

CR-2SW-PB

Countertop Push Button Chilled Still Water Dispenser



Commercial countertop push-button beverage dispensing unit that provides chilled still water. Self-contained refrigeration with European design stainless steel exterior. Suitable for high-volume self-service stations and hospitality applications.

Features

- Up to 68 liters/hour (<40°F)
- Dual-water dispensing (chilled still)
- High-efficiency self-contained refrigeration
- Durable 304 stainless steel exterior*
- Bottle fill station with 11" clearance
- Push button dispensing

Accessories

- Water filter system (required):
 - CR-24FC: Twin filter system, compact fibredyne filters, reduce chlorine, taste, odor, color while retaining the good minerals that are essential for bottle quality tasting water, 19"H x 17"W, 5 gpm, 30,000 gal, TOC & ½ micron filtration
 - CR-24FCP: Twin filter system with prefilter, compact fibredyne filters, reduce chlorine, taste, odor, color and organic chemicals while providing exceptional sediment reduction with resistance to premature plugging, 19.25"H x 21.75"W, 5 gpm, 30,000 gal, TOC & ½ micron filtration
- Install kit (required):
 - CR-KIT-SWCT: Installation kit for countertop still water units, CR-1SW & CR-2SW, includes fittings and oetiker clamps and extra tubing to install the filter systems and countertop unit




CR-2SW-PB

Countertop Push Button Chilled Still Water Dispenser



Scan for more resources!

Line Drawings



- 3/8" Water inlet push in fitting at bottom of machine
- 7' Over flow drain hose
- 9' Electrical cord NEMA 5-15
- 4.0" - 5.5" adjustable legs
- Air intake at rear with air filter
- Allow for 6" side clearance for air flow out
- Allow for 3" of rear clearance for air flow in

Capacity	68 liters/hour (<40°F)
Refrigerant	R290
Width	20"
Depth	26"
Height	24.75"
Bottle fill clearance	11"
Compressor	1/3 H.P.

Operating temp	40°F-100°F
Electrical	120v - 8.4 Amps
BTU Output	~2,600 BTU/hr
Water bath	6 gal
Ice bank	25 lbs
Weight	135 lbs